

從資料整理開始 打好精準醫學研究根基

國立中山大學


馮己榕

ijfeng@g-mail.nsysu.edu.tw




醫學生物技術暨檢驗學系 (含碩士班)
Department of Medical Biotechnology and Laboratory Science, CGU
Graduate Institute of Medical Biotechnology and Laboratory Science

醫事檢驗 醫學 生物科學



Department of Population and Quantitative Health Sciences


生物統計
微積分 線性代數 數理統計
寫程式 SAS、R、Matlab
醫學影像



動物實驗
整形外科病例登錄



人工智慧 機器學習 深度學習
Python



什麼是醫學(medicine)?

Predict

Disgnose

Treat

Monitor

如何預防?

Predict

Disgnose

Treat

Monitor

心肌梗塞的危險因子 你中了幾個?

- 年齡 男性>45歲或女性>55歲(或停經)
- 性別 男性>女性
- 三高 高血壓、高血糖、高血脂
- 家族史
- 吸菸、吸二手菸
- 久坐不動、活動量少
- 某些藥物 避孕藥和激素替代療法 (HRT)



Hb 健康吉美健檢中心
H&B HEALTH CENTER

健康傳媒
Health Media

如何預防失智症



保護因子

危險因子

如何診斷?

Predict

Disgnose


Treat

Monitor


- 症狀
- 身體檢查 {性別、年齡、身高、體重、心跳、血壓...}
- 病史
- 家族史
- 病理中心檢驗數據 {血液常規檢查 (白血球、紅血球、血色素...)、生化檢查(糖化血色素、膽固醇...)、血清學檢查...}
- 醫療影像{x-ray、CT、MRI...}




如何診斷?



- 症狀 - 腹部疼痛，有時甚至會感到胸部或右肩胛骨疼痛，無論如何改變姿勢都無法減輕疼痛。
- 身體檢查 -
 - 大於40歲
 - 女性
 - 肥胖者 (BMI > 30)
- 病史
- 家族史-有膽結石家族
- 病理中心檢驗數據
- 醫療影像 - 腹部X光檢查、電腦斷層掃描或腹部超音波



膽結石



如何診斷？


Predict

Disgnose

Treat


Monitor

- 症狀 - 尿多、口渴、飢餓、疲勞、視力模糊、體重減輕或傷口不易癒合
吃多、喝多、尿多 + 體重減少 (三多一少)
- 身體檢查 - 40歲以上? 肥胖?
- 病史
- 家族史 - ?
- 病理中心檢驗數據 –
 1. 隨機血漿糖值 (無論空腹與否的任意時間測得的血糖值) ≥ 200 (單位 : mg/dl, 毫克/分公升)
 2. 空腹8小時後血糖 ≥ 126 mg/dl。
 3. 空腹口服75公克葡萄糖後測試 (此檢查稱為葡萄糖耐受試驗) , 在2小時的血糖值 ≥ 200 mg/dl。
 4. 糖化血色素 (HbA1C) $\geq 6.5\%$ 。
- 醫療影像




第2型糖尿病


如何診斷?



- 症狀-
發燒($\geq 38^{\circ}\text{C}$)
急性呼吸道感染或嗅、味覺異常。
 - 身體檢查
 - 病史
 - 家族史
 - 病理中心檢驗數據 –
 1. 臨床檢體(如鼻咽或咽喉擦拭液、痰液或下呼吸道抽取液等)分離並鑑定出**新型冠狀病毒**。
 2. 臨床檢體**新型冠狀病毒**分子生物學核酸檢測陽性。
- 醫療影像**
放射線診斷顯示有肺炎。




COVID-19
(武漢肺炎)



如何治療？




膽結石



膽囊切除手術

第2型糖尿病



胰島素/
降血糖藥物


糖尿病指的是人體內的胰臟不能製造足夠的胰島素，導致葡萄糖無法充分進入細胞內，血糖濃度就會升高形成糖尿病。

財團法人蘭陽仁愛醫院 - 糖尿病

COVID-19



呼吸器



如何追蹤？



- 症狀
- 身體檢查 {性別、年齡、身高、體重、心跳、血壓...}
- 病史
- 家族史
- 病理中心檢驗數據 {血液常規檢查(白血球、紅血球、血色素...)、生化檢查(糖化血色素、膽固醇...)、血清學檢查...}
- 醫療影像{x-ray、CT、MRI...}

傳統研究方式

Koch's postulates

描述疾病（通常是傳染病）與病原菌之間因果關係的條件



德國醫師 / 生理學家 Robert Koch。
Image courtesy of Nobelprize.org

1. 病體身上可以找到大量致病病原菌，而在健康活體上找不到這些病原菌。
2. 這些病原菌可以從病體身上分離出，而且可以在適當的培養基上生長。
3. 培養出的病原菌可以造成原本健康的活體患病。
4. 從這些因為接種了培養出的病原菌而患病的病體身上，可以再次分離出和原先培養一樣的病原菌菌種。


Koch's Postulates:



① The microorganism must be found in abundance in all organisms suffering from the disease, but should not be found in healthy organisms.

② The microorganism must be isolated from a diseased organism and grown in pure culture.

③ The cultured microorganism should cause disease when introduced into a healthy organism.


④ The microorganism must be reisolated from the inoculated, diseased experimental host and identified as being identical to the original specific causative agent.







研究方式

“年齡”是否與“聽過鋼彈”相關？





“年齡”是否與“喜歡鋼彈”相關？



“性別”是否與“膽結石”相關?

“年齡”是否與“膽結石”相關?

“肥胖”是否與“膽結石”相關?




Multivariable thinking 多項思考

Does Taking Your Time in College Pay Off?


-- 2016 AP Statistics Exam

“A newspaper in Germany reported **that the more semesters need to complete an academic program at the university, the greater the starting salary in the first year of a job.** The report was based on a study that used a random sample of 24 people who had recently completed an academic program. Information was collected on the number of semesters each person in the sample needed to complete the program and the starting salary, in thousands of euros, for the first year of a job.”



a. Does the scatterplot **support** the newspaper report about number of semesters and starting salary?

“An independent researcher received the data from the newspaper and conducted a new analysis by separating the data into three groups based on the major of each person. A revised scatterplot identifying the major of each person is shown below.”



c. Based on the people in the sample, **describe the relationship between starting salary and number of semesters for the business majors.**

e. Based on the analysis conducted by the independent researcher, how could the newspaper report be **modified to give a better description** of the relationship between the number of semesters and the starting salary for the people in the sample?


Multivariable thinking

Confounding Variables




A Concern in Observational Studies and Poorly Designed Experiments

Are the variables of a child's shoe size and their reading ability correlated?

Shoe size	Reading ability
4	4
5	5
6	7
4	5
5	4
6	5
4	4
5	4
6	6
7	8
8	9
9	9
7	8
8	7
9	7
2	1
3	2
4	4
2	1
3	2
4	4




Crime rate and ice cream sales





Confounding Variables

A Concern in Observational Studies and Poorly Designed Experiments



There is a **strong positive relationship** between **number of televisions per household** and **life expectancy** for countries in the world.



新研究工具

2016年韓國棋王李世乜代表人類出戰Google DeepMind開發的AlphaGo




【纪录片】AlphaGo世紀對決 2017_剪接

Artificial intelligence is the field of computer science that is associated with the concept of machines “**think like humans**” to perform tasks such as **learning, problem-solving, planning, reasoning and identifying patterns.**

1950

圖靈測試 (Turing test)

判斷機器是否能夠思考的實驗



Timeline of artificial intelligence

Antiquity
In **Greek mythology**, **Talos** was a giant automaton made of bronze to protect Europa

1950
Asimov introduced the **Three Laws of Robotics**

1956
Arthur Samuel (IBM) wrote the **first game-playing program** for checkers
John McCarthy coins “**Artificial Intelligence**” for the first time

1980
Generation of entrepreneurs believed AI was the **wave of the future**

1985
Computer Scientists pioneer **highly effective ML method**

2010
ImageNet Challenge


2015
Google DeepMind's **AlphaGo** defeats European Go champion

2016
Microsoft's AI can now understand speech **better than humans**

2017
AI **'everywhere'** and accelerating

ImageNet Error Rate
Graph showing error rate decreasing from ~28% in 2010 to ~5% in the present, with a note: "Using deep learning" and "Normal performance" at ~5%.

Hot terms
Number of USPTO average calls using select keywords, by quarter. Graphs for: artificial intelligence, autonomous vehicles, data analysis, machine learning.



2015 AlphaGo 5:0 歐洲圍棋冠軍樊麾二段
2016 AlphaGo 4:1 世界冠軍韓國職業棋士李世石九段


人工智慧:

計算機模仿人類思考進而模擬人類的能力/行為。

傳統規則式專家系統 (rule-based expert system)

輸入了人類的200多萬局棋譜
計算出每一步棋後面的12步變化
最強的人類只能計算10步

專家系統是一個知識庫(Knowledge-based)，設計
用來解決特定領域(Specific domain)的問題



深藍 (Deep Blue)
專門分析西洋棋

許峰雄
生於台灣基隆
1980年畢業於臺灣大學電機系
1989年獲得美國卡內基美隆大學電腦科學博士學位

分辨貓或是狗

專家系統:

狗是汪汪叫，貓是喵喵叫
狗比較大隻，貓比較小隻



鼻子形狀

腳印




機器學習 (Machine Learning)

經過資料觀察，特徵萃取，模型建立的過程得到可以歸納/學習出有用規則的模型


資料結構化:

- 身高
- 體重
- 性別
- 毛髮顏色
- 花紋有無
- 叫聲
- 鼻子形狀
- ：
- 飼養者每月平均花費
- 每年上動物醫院院次數
- 每年上動物美容院次數





特徵提取 (feature extraction):
選入幫助模型進行決策(提高分類/預測準確度)的變項


ID	H	W	label
001	8	8	DOG
002	40	50	DOG
:			
999	9	8	CAT




深度學習 (Deep Learning)




電腦看到什麼 - 電腦視覺 (Computer vision)



1個像素 (pixel)




Links carry signals from one node to another, boosting or damping them according to each link's 'weight'.



157	153	174	168	150	152	129	151	172	161	155	156
155	182	163	74	75	62	33	17	110	210	180	154
180	180	50	14	34	6	10	33	48	106	159	181
206	109	5	124	131	111	120	204	166	15	56	180
194	68	137	251	237	239	239	228	227	87	71	201
172	105	207	233	233	214	220	239	228	98	74	206
188	88	179	209	185	215	211	158	139	75	20	169
189	97	165	84	10	168	134	11	31	62	22	148
199	168	191	193	158	227	178	143	182	106	36	190
205	174	155	252	236	231	149	178	228	43	95	234
190	216	116	149	236	187	85	150	79	38	218	241
190	224	147	108	227	210	127	102	36	101	255	224
190	214	173	66	103	143	96	50	2	109	249	215
187	196	235	73	1	81	47	0	6	217	255	211
183	202	237	145	0	0	12	108	200	138	243	236
195	206	123	207	177	121	123	200	175	13	96	218

157	153	174	168	150	152	129	151	172	161	155	156
155	182	163	74	75	62	33	17	110	210	180	154
180	180	50	14	34	6	10	33	48	106	159	181
206	109	5	124	131	111	120	204	166	15	56	180
194	68	137	251	237	239	239	228	227	87	71	201
172	105	207	233	233	214	220	239	228	98	74	206
188	88	179	209	185	215	211	158	139	75	20	169
189	97	165	84	10	168	134	11	31	62	22	148
199	168	191	193	158	227	178	143	182	106	36	190
205	174	155	252	236	231	149	178	228	43	95	234
190	216	116	149	236	187	86	150	79	38	218	241
190	224	147	108	227	210	127	102	36	101	255	224
190	214	173	66	103	143	96	50	2	109	249	215
187	196	235	73	1	81	47	0	6	217	255	211
183	202	237	145	0	0	12	108	200	138	243	236
195	206	123	207	177	121	123	200	175	13	96	218

12 X 17 像素 (pixel)



224 X 300 像素 (pixel)

Blue channel

Green channel


Red channel

		171	200	19	6	...	26	
1	120	67	89	107	...	13	18	89
2	12	216	145	26	...	181	8	8
3	0	16	4	45	...	44	81	71
4	0	78	90	167	...	25	56	...
...	7
64	12	67	82	141	...	12	12	...
	1	2	3	4	...	64		

Image array: [64 x 64 x 3]

亞伯拉罕·林肯，第十六任美國總統

1980S-ERA NEURAL NETWORK



Links carry signals from one node to another, boosting or damping them according to each link's 'weight'.

DEEP LEARNING NEURAL NETWORK






Image recognition: Pixel → edge → texton → motif → part → object


Airedale, Airedale terrier




miniature schnauzer




Boston bull, Boston terrier



standard poodle



English setter



萬能梗
(Airedale Terrier)


迷你雪納瑞
(Miniature Schnauzer)

波士頓梗
(Boston Terrier)


標準貴賓犬
(Standard Poodle)

英國蹲獵犬
(English Setter)


Input




Ink \rightarrow 1
No ink \rightarrow 0



What is needed is a function




Output



Each dimension represents the confidence of a digit.

深度學習 學到什麼?

8 2 7 7 5 7 7 2 8 8 5 7 0 7 1 7 5 9 3 1 0 2 7 9 9 6 9 4 7 4 1 1 4 4 8 8 0 2 6 3
0 0 7 6 3 4 4 4 3 4 2 3 2 8 0 8 2 9 7 6 7 9 0 0 4 2 0 6 6 4 3 3 9 0 4 7 3 2 2 0
2 6 4 6 4 7 5 9 8 7 1 9 0 6 4 7 7 1 9 8 6 5 7 1 0 1 0 8 3 4 7 7 1 3 0 9 6 0 3 8
0 2 8 3 6 5 7 6 6 7 2 6 1 0 2 6 9 7 1 9 5 8 7 0 0 6 1 6 4 4 8 6 2 3 3 1 3 9 9 4
5 1 0 2 9 4 2 2 0 9 9 9 3 1 3 4 1 9 5 5 4 3 9 3 3 5 8 5 0 6 5 1 8 2 6 8 9 2 2 8
4 7 7 7 5 5 0 7 2 2 1 3 5 8 4 8 8 5 2 5 7 1 6 1 8 3 8 0 0 1 0 3 6 2 4 0 8 6 6 2
1 3 3 9 0 4 9 7 5 4 9 5 5 2 6 9 5 3 4 7 3 0 4 6 2 9 4 0 6 2 7 1 0 3 9 1 2 6 0 6
3 4 1 1 9 0 8 2 1 1 9 0 7 5 7 4 2 3 9 9 9 0 2 5 2 1 3 8 3 3 1 6 7 6 0 7 2 0 0 5
7 1 3 1 2 8 8 2 9 4 4 2 4 7 9 8 4 8 0 3 0 7 8 8 3 9 4 7 3 3 1 6 0 8 7 2 1 1 6 2
6 0 1 7 2 3 6 1 6 5 0 7 8 7 8 6 9 2 3 8 8 6 5 1 1 3 2 6 0 6 0 5 9 9 1 0 2 2 1 9



Deep learning can be highly flexible

- Speech Recognition

$$f^* \left(\text{[Waveform]} \right) = \text{"Morning"}$$

- Handwritten Recognition

$$f^* \left(\text{[Handwritten '2']} \right) = \text{"2"}$$


- Playing Go

$$f^* \left(\text{[Go board]} \right) = \text{"5-5"} \\ \text{(step)}$$

- Dialogue System

$$f^* \left(\text{"Hi"} \right) = \text{"Hello"}$$

(what the user said) (system response)





Dog or Mop?



Pug or Croissant?



吉娃娃 OR 瑪芬

New tool + Big data → New finding

馮已榕


長庚大學 醫學生物技術暨檢驗學系
凱斯西儲大學 (Case Western Reserve University)
生物統計碩士/博士



搖滾名人堂



Cuyahoga Valley National Park



America's favorite pies



南瓜派



胡桃派




檸檬派 (ley lime pie)



蘋果派



櫻桃派



More data → New finding



定位紀錄, 心跳, 心電圖



汽車防盜系統



斐斯托斯圓盤
Phaistos Disc



5D optical data storage
360TB, 189 °C 保存138億年

More data → better finding ?




王聖捷
Tricia Wang

- 知道智慧型手機的族群
- 不知道智慧型手機的族群




NOKIA




貴，一摔就壞，重

Know your data
know your question



Ref: NYTimes.com

<https://www.nytimes.com/interactive/2016/07/05/upshot/is-sushi-healthy-what-about-granola-where-americans-and-nutritionists-disagree.html#:~:text=No%20food%20elicited%20a%20greater,30%20percent%20of%20nutritionists%20did.>



Variables:


- Percentage of **nutritionists** saying a food is healthy.
- Percentage of **all Americans** saying a food is healthy.
- Food

Ref: NYTimes.com

<https://www.nytimes.com/interactive/2016/07/05/upshot/is-sushi-healthy-what-about-granola-where-americans-and-nutritionists-disagree.html#:~:text=No%20food%20elicited%20a%20greater,30%20percent%20of%20nutritionists%20did.>




- What do you notice?
- What do you wonder?
- What kind of headline would you write for this graph?



Ref: NYTimes.com

<https://www.nytimes.com/interactive/2016/07/05/upshot/is-sushi-healthy-what-about-granola-where-americans-and-nutritionists-disagree.html#:~:text=No%20food%20elicited%20a%20greater,30%20percent%20of%20nutritionists%20did.>



Foods considered healthier by the public than by experts

	Percent describing a food as "healthy"	Nutritionists	Public	Difference
Granola bar	28%	28%	71%	43
Coconut oil	37%	37%	72%	35
Frozen yogurt	32%	32%	66%	34
Granola	47%	47%	80%	33
SlimFast shake	21%	21%	47%	26
Orange juice	62%	62%	78%	16
American cheese	24%	24%	39%	15

SlimFast Shake 代餐奶昔: 4克脂肪，1克飽和脂肪，30克碳水化合物，4克纖維，22克糖，10克蛋白質

I Can't Believe It's Yogurt!



BBC中文網

BBC試驗：椰子油是超級食品還是心臟病殺手？

許多科學家都對椰子油的健康療效持懷疑態度。不僅如此，科學界還把椰子油看作是壞脂肪，因為它富含飽和脂肪（86%），遠遠高...

Jan 9, 2018

TVBS新聞

椰子油是好油還是毒藥？國健署闢謠，預防失智多運動、多動腦較實在

網傳椰子油對身體很好，但也有人說是毒藥，到底哪個才正確？國健署指出，椰子油有90%是飽和脂肪酸，吃太多容易造成心血管疾病風險，民眾

Cosmopolitan HK

椰子油8大美容功效：抗衰老、美白牙齒、護髮、排毒...女星們...

椰子油其實是從椰果肉中提煉出來的油脂，當中含有豐富的月桂酸（lauric acid），它是一種...

Oriental Sunday More

油拔法：用椰子油漱口可排毒、美白牙齒！天后鄭秀文和容祖兒...

椰子油漱口又稱「油拔法」（英文：oil pulling），是一種源自古印度阿育吠陀（Ayurveda）的天然療法，一直流傳至今。到90年代初，由一位名...

2 weeks ago



整理資料



衛生福利部
Ministry of Health and Welfare

2019 建構精準 健康照護體系高峰會議

Taiwan Precision Health System Summit

**Drive progress
Precision Medicine 2030**

Genome Sequencing and Big Data in Health Care
Health Care Database and Data Standardization
Health Industry Development

MEDTECH⁺

— 未來城市FUTURECITY · 智慧醫療 —

#2 我們的未來醫生

未來競爭力

不在醫院的大小，而是資料的完整性跟正確性。



北醫院長

陳瑞杰



Essay

Why Most Published Research Findings

Are False

John P. A. Ioannidis, PLoS Med. 2005 Aug

John P. A. Ioannidis


醫學假設 $\checkmark \rightarrow$ 實驗證實 $? \rightarrow$ 現實生活




Garbage In Garbage Out



DATA





Model




Result




shutterstock.com · 133381535



shutterstock.com · 133381535




shutterstock.com · 133381535



shutterstock.com · 133381535

就醫流程



入院護理紀錄

病歷號	年齡	性別	婚姻狀況	教育程度
1234567	60	男	鰥寡	小學
1234578	64	男	新婚	10年
2546871	99	女	已婚	大專以上

入院醫生診斷


床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	診斷碼1	診斷碼2	診斷碼3	診斷碼4
1	1234567	2020/06/12	1960/05/01	高血壓	腦血管疾病	心臟疾病	子宮頸惡性腫瘤
2	1234578	2020/06/31	1955/11/24	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	2008/02/09	糖尿病	心臟疾病		

入院醫生處置

床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	藥碼1	藥碼2	藥碼3	藥碼4
1	1234567	2020/06/12	1960/05/01	B01	B05	B05	A03
2	1234578	2020/06/31	1955/11/24	A03	B05	A04	M04
3	2546871	2020/07/01	2008/02/09	A03	M04	A04	R06



各檔案間串檔變項說明



註:*須注意生效起訖日期
(2)可由ID+BIRTHDAY串檔

→ 各檔案間由所註明變項串檔可獲得對應資訊
→ 各檔案間可由所註明變項串檔,但未必獲得對應資料

變項類型

- **連續[量]**: 小數點有意義的數字

Ex., 血清總膽固醇濃度(mg / dl), 溫度(攝氏), BMI(kg/m²)...

- **序數**: 有順序上的關係, 但沒有數學上倍數的關係

Ex., [冠軍, 亞軍, 季軍] [低年級, 中年級, 高年級] 疼痛指數
滿意度[很滿意, 滿意, 尚可, 不滿意, 很不滿意]



- **類別[質]**: 沒有大小關係

二項: 只有兩個類別

Ex., [死亡/存活] [男/女][有/沒有 糖尿病]
[有/沒有 抽菸]

非二項: 兩個以上類別

Ex., 血型[A型, B型, AB型, O型]
種族[高加索人, 非洲人, 亞洲人]

- **時間(天)** – 開始治療後到死亡, 診斷後到復發

資料整理

資料整理

床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	診斷碼1	診斷碼2	診斷碼3	診斷碼4
1	1234567	2020/06/12	1960/05/01	60	男	鰥寡	小學	高血壓	腦血管疾病	心臟疾病	子宮頸惡性腫瘤
2	1234578	2020/06/31	1955/11/24	64	男	新婚	10年	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	2008/02/09	99	女	已婚	大專以上	糖尿病	心臟疾病		

1. 數值是否符合一般(醫學)認知?

床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	診斷碼1	診斷碼2	診斷碼3	診斷碼4
1	1234567	2020/06/12	1960/05/01	60	男	鰥寡	小學	高血壓	腦血管疾病	心臟疾病	子宮頸惡性腫瘤
2	1234578	2020/06/31	1955/11/24	64	男	新婚	10年	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	2008/02/09	32	女	已婚	大專以上	糖尿病	心臟疾病		

12?

未婚	小學
已婚	國中
鰥寡	高中
離婚	大專以上
其他	其他

資料整理

床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	診斷碼1	診斷碼2	診斷碼3	診斷碼4
1	1234567	2020/06/12	1960/05/01	60	男	鰥寡	小學	高血壓	腦血管疾病	心臟疾病	子宮頸惡性腫瘤
2	1234578	2020/06/31	1955/11/24	64	男	新婚	10年	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	2008/02/09	32	女	已婚	大專以上	糖尿病	心臟疾病		

Raw data



床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	診斷碼1	診斷碼2	診斷碼3	診斷碼4
1	1234567	2020/06/12	1960/05/01	60	男	鰥寡	小學	高血壓	腦血管疾病	心臟疾病	子宮頸惡性腫瘤
2	1234578	2020/06/31	1955/11/24	64	男	已婚	國中	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	1988/02/09	32	女	已婚	大專以上	糖尿病	心臟疾病		

Step 1 除錯

資料整理

床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	診斷碼1	診斷碼2	診斷碼3	診斷碼4
1	1234567	2020/06/12	1960/05/01	60	男	鰥寡	小學	高血壓	腦血管疾病	心臟疾病	
2	1234578	2020/06/31	1955/11/24	64	男	已婚	國中	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	1988/02/09	32	女	已婚	大專以上	糖尿病	心臟疾病		



床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	高血壓	腦血管疾病	糖尿病	心臟疾病	氣喘
1	123456 7	2020/06/12	1960/05/01	60	男	鰥寡	小學	1	1	0	1	0
2	123457 8	2020/06/31	1955/11/24	64	男	已婚	國中	1	0	1	0	1
3	254687 1	2020/07/01	1988/02/09	32	女	已婚	大專以上	0	0	1	1	0

Step2 : 整理架構

資料整理

床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	診斷碼1	診斷碼2	診斷碼3	診斷碼
1	1234567	2020/06/12	1960/05/01	60	男	鰥寡	小學	高血壓	腦血管疾病	心臟疾病	
2	1234578	2020/06/31	1955/11/24	64	男	已婚	國中	高血壓	糖尿病	氣喘	
3	2546871	2020/07/01	1988/02/09	32	女	已婚	大專以上	糖尿病	心臟疾病		




床號	病歷號	住院日 (yyyy/mm/dd)	出生年月日 (yyyy/mm/dd)	年齡	性別	婚姻狀況	教育程度	高血壓	腦血管疾病	糖尿病	心臟疾病	氣喘
1	1234567	2020/06/12	1960/05/01	60	1	3	1	1	1	0	1	0
2	1234578	2020/06/31	1955/11/24	64	1	2	2	1	0	1	0	1
3	2546871	2020/07/01	1988/02/09	32	2	2	4	0	0	1	1	0

Step3 : coding book

1,男	1,未婚	1,小學	0,無
2,女	2,已婚	2,國中	1,有
	3,鰥寡	3,高中	
	4,離婚	4,大專以上	
	5,其他	5,其他	

資料結構邏輯



露比任務：培養孩子邏輯思考的程式尋寶記

字串、數字、布林值(booleans)

字串：只要能被包括在引號裡的符號都算是字串, 他可能包含了字母、數字、空白, 或是其他電腦鍵打得出來的符號, 像是" Ruby" .

數字：像是1、2、3, 或是 4.1217.

布林值(booleans)：他只有「真」(True) 或是「假」(False)兩種表達方式



I'm red and yellow.
I'm pink and green.
I'm happy.

True/False
True/False
True/False



My eyes are green.
I have six points.
I am not yellow.

True/False
True/False
True/False




I have legs.
I have arms and legs.
I have arms or legs.


True/False
True/False
True/False

資料結構 (data structure)

資料結構 (data structure) : 資料有許多型態. 像是字串、數字與布林值. 當手上有非常多資料時, 把他們排列的有條有理, 會大大的提升使用效率. 我們將這個方法稱之為「資料結構」 (data structure).







Pear



Broccoli



Carrot



Orange





Apple



Mushrooms

Zip



Everything else

		水果	橘色
1			
2			
3			
4			
5			
6			

		水果	橘色
1		+	-
2		-	-
3		-	+
4		+	+
5		+	-
6		-	-

True / False

		水果	橘色	水果 且 橘色
1		+	-	
2		-	-	
3		-	+	
4		+	+	
5		+	-	
6		-	-	

True / False

		水果	橘色	水果 且 橘色
1		+	-	False
2		-	-	False
3		-	+	False
4		+	+	True
5		+	-	False
6		-	-	False

True / False

		水果	橘色	水果 或 橘色
1		+	-	
2		-	-	
3		-	+	
4		+	+	
5		+	-	
6		-	-	

True / False

		水果	橘色	水果 或 橘色
1		+	-	True
2		-	-	False
3		-	+	True
4		+	+	True
5		+	-	True
6		-	-	False

True / False

		水果	橘色	水果 且 不是橘色
1		+	-	
2		-	-	
3		-	+	
4		+	+	
5		+	-	
6		-	-	

True / False

		水果	橘色	水果 且 不是橘色
1		+	-	True
2		-	-	False
3		-	+	False
4		+	+	False
5		+	-	True
6		-	-	False

True / False

True / False


True / False

	水果	橘色	水果 且 橘色	水果 或 橘色	水果 且 不是橘色	
1		+	-	False	True	True
2		-	-	False	False	False
3		-	+	False	True	False
4		+	+	True	True	False
5		+	-	False	True	True
6		-	-	False	False	False


迴圈 (loop)



This is how a fox would plant an entire row of carrots.



This is how a fox would plant an entire row of carrots.




選擇

「如果...,就...」(if-then)

2




One piece of instruction has gone missing. Can you figure out which one?



3



The foxes came up with a shorter way to write the instructions. Can you help them fill in the code?



選擇

「如果...,就...」(if-then)



4 Many things are missing from this piece of instruction. Can you figure it out?



5 You know how to do this already!


選擇

「如果...,否則...」(if-else)

6



Oops, there's a bug in the row. What should you do to it?






7

How would you instruct the Foxes to plant this row? Pay close attention to the word *not*.

7




How would you instruct the Foxes to plant this row? Pay close attention to the word *not*.



Acute Inflammations Data Set

J.Czerniak, H.Zarzycki, Application of rough sets in the presumptive diagnosis of urinary system diseases, Artificial Intelligence and Security in Computing Systems, ACS'2002 9th International Conference Proceedings, Kluwer Academic Publishers,2003, pp. 41-51



腎盂腎炎
Nephritis of renal pelvis origin

- 常發生在女性
- 突然高燒，體溫常超過40°C
- 高燒伴隨顫抖、雙邊或單側的腰椎異常疼痛
- 排尿疼痛
- 可能不規律的發生噁心、嘔吐、腹部疼痛




急性膀胱炎
Inflammation of urinary bladder

- 突發性腹部疼痛
- 常見排尿困難、排尿疼痛、頻尿
- 體溫升高，但常不超過38°C
- 排出尿液混濁，有時會有血尿

資料整理

{共120個觀察值, 6個變項, 其中一個連續型變項, 5個類別變項}

Temperature 體溫	Nausea 噁心	Lumbar pain 腰椎痛	Urine pushing 排尿困難	Micturition pains 排尿疼痛	Burning of urethra 尿道灼熱, 搔癢
35,5	no	yes	no	no	no
35,9	no	no	yes	yes	yes
35,9	no	yes	no	no	no
36,0	no	no	yes	yes	yes
36,0	no	yes	no	no	no



,	→	.
yes	→	1
no	→	0

Coding book

變項編號	變項英文名稱	變項中文名稱	單位	
V1	Temperature	體溫	°C	連續變項
V2	nausea	噁心		0:無(no) 1:有(yes)
V3	Lumbar pain	腰椎痛		0:無(no) 1:有(yes)
V4	Urine pushing	排尿困難		0:無(no) 1:有(yes)
V5	Micturition pains	排尿疼痛		0:無(no) 1:有(yes)
V6	Burning of urethra	尿道灼熱, 搔癢		0:無(no) 1:有(yes)

Alt+Enter : 下一行

AND、OR、NOT

Temperature 體溫	Nausea 噁心	Lumbar pain 腰椎痛	Urine pushing 排尿困難	Micturition pains 排尿疼痛	Burning of urethra 尿道灼熱, 搔癢
35,5	no	yes	no	no	no
35,9	no	no	yes	yes	yes
35,9	no	yes	no	no	no
36,0	no	no	yes	yes	yes
36,0	no	yes	no	no	no

腎盂腎炎

Nephritis of renal pelvis origin

- 常發生在女性
- 突然高燒，體溫常超過40°C
- 高燒伴隨顫抖、雙邊或單側的腰椎異常疼痛
- 排尿疼痛
- 可能不規律的發生噁心、嘔吐、腹部疼痛

急性膀胱炎

Inflammation of urinary bladder

- 突發性腹部疼痛
- 常見**排尿困難**、**排尿疼痛**、頻尿
- 體溫升高，但常不超過38°C
- 排出尿液混濁，有時會有血尿

Cystitis_1



排尿困難且排尿疼痛

Cystitis_2


排尿困難或排尿疼痛或尿道灼熱



Microsoft Excel



SPSS





SAS Enterprise Guide

File Edit View Tasks Favorites Program Tools Help

Project Tree

- Process Flow
 - Programs
 - Program

Servers

Refresh Disconnect

- Servers
- Private OLAP Servers


Program

Save Run Stop Selected Server: Local Analyze Program Export Send To Create

```
LIBNAME mylib 'C:\My SAS Files';  
*Separate countries with medals from those without;  
DATA winners nomedals; SET mylib.olympics;  
IF TotalMedals>0 THEN DO;  
TotalRatio=TotalMedals/TotalAthletes;  
GoldRatio=Gold/TotalAthletes;  
SilverRatio=Silver/TotalAthletes;  
BronzeRatio=Bronze/TotalAthletes;  
OUTPUT winners; END; ELSE OUTPUT nomedals;  
RUN; PROC MEANS DATA=winners;  
TITLE 'Ratio of Medals to Participants';  
VAR TotalRatio GoldRatio SilverRatio BronzeRatio;  
RUN;  
PROC SGPLOT DATA=winners;  
TITLE 'Olympic Medal Count for Countries';  
SCATTER X=TotalAthletes Y=TotalMedals;
```


Undo Ctrl+Z
Redo Ctrl+Y
Cut Ctrl+X
Copy Ctrl+C
Paste Ctrl+V
Delete Del
Select All Ctrl+A
Format Code Ctrl+I
Export As HTML
Copy HTML Source to Clipboard
Split
Run On Local
Run Selection On Local
Select Server
Properties

Ready Line 4, Col 26 100% No profile selected



The image shows a Jupyter Notebook window with the following elements:

- Menu Bar:** File, Edit, View, Run, Kernel, Tabs, Settings, Help.
- File Explorer:** A sidebar on the left with icons for home, run, palette, settings, and a document.
- Tab:** A single tab titled "first_notebook.ipynb" is open.
- Toolbar:** A row of icons for saving, adding, deleting, copying, pasting, running, and refreshing. The text "Code" and a dropdown arrow are also present. On the right, it says "Python 3" with a refresh icon.
- Code Cell:** A code cell containing the Python code `[1]: print("Hola World!!")`. The code is highlighted in a light gray box.
- Output:** Below the code cell, the text "Hola World!!" is displayed as the output of the code.
- Input Cell:** Below the output, there is an empty code cell with the prompt `[]:` and a vertical cursor.



R software



r



R



[All](#) [Images](#) [Maps](#) [Videos](#) [News](#) [More](#)

[Settings](#) [Tools](#)

About 13,570,000,000 results (0.71 seconds)

[www.r-project.org](#)

The R Project for Statistical Computing

R is a free software environment for statistical computing and graphics.

Results from r-project.org



CRAN

CRAN is a network of ftp and web servers around the world that ...

CRAN - Mirrors

CRAN - Mirror HOWTO - Status - ...

Windows

R-4.0.3 for Windows (32/64 bit).
Download R 4.0.3 for Windows ...

The R Foundation

The R Foundation · Provide support for the R project and ...

About R

There are about eight packages supplied with the R distribution ...

Of /src/base/R-4

Index of /src/base/R-4. [ICO],
Name · Last modified · Size ...

[en.wikipedia.org](#) › [wiki](#) › [R_\(programming_language\)](#)

R (programming language) - Wikipedia

R is a programming language and free software environment for statistical computing and graphics supported by the R Foundation for Statistical Computing.

Developer: R Core Team

Designed by: Ross Ihaka and Robert Gent...

Paradigms: Multi-paradigm: Array, object-orie...

Stable release: 4.0.3 / 10 October 2020; 2...



R

Programming language

R is a programming language and free software environment for statistical computing and graphics supported by the R Foundation for Statistical Computing. The R language is widely used among statisticians and data miners for developing statistical software and data analysis. [Wikipedia](#)

Stable release: 4.0.3 / 10 October 2020; 23 days ago

First appeared: August 1993; 27 years ago

Typing discipline: Dynamic

License: GNU GPL v2

Filename extensions: .rdata.rds.rda

Designed by: Ross Ihaka, Robert Gentleman

People also search for

[View 10+ more](#)



[\[Home\]](#)

Download

[CRAN](#)

R Project

[About R](#)

[Logo](#)

[Contributors](#)

[What's New?](#)

[Reporting Bugs](#)

[Conferences](#)

[Search](#)

[Get Involved: Mailing Lists](#)

[Developer Pages](#)

[R Blog](#)

R Foundation

[Foundation](#)

[Board](#)

[Members](#)

[Donors](#)

[Donate](#)

Help With R

[Getting Help](#)

Documentation

[Manuals](#)

[FAQs](#)

[The R Journal](#)

[Books](#)

[Certification](#)

[Other](#)

Links

[Bioconductor](#)

[Related Projects](#)

[GSoC](#)

The R Project for Statistical Computing

Getting Started

R is a free software environment for statistical computing and graphics. It compiles and runs on a wide variety of UNIX platforms, Windows and MacOS. To [download R](#), please choose your preferred CRAN mirror.

If you have questions about R like how to download and install the software or what the license terms are, please read our [answers to frequently asked questions](#) before you send an email.

News

- [R version 4.0.3 \(Bunny-Wunnies Freak Out\)](#) has been released on 2020-10-10.
- Thanks to the organisers of useR! 2020 for a successful online conference. Recorded tutorials and talks from the conference are available on the [R Consortium YouTube channel](#).
- [R version 3.6.3 \(Holding the Windsock\)](#) was released on 2020-02-29.
- You can support the R Foundation with a renewable subscription as a [supporting member](#)

News via Twitter



The R Foundation

@_R_Foundation



New R blog entry by Tomas Kalibera and Simon Urbanek. Will R work on Apple Silicon?[developer.r-project.org/Blog/public/20...](#)



Nov 2, 2020



The R Foundation Retweeted



R Consortium

@RConsortium

Deadline is Oct 1! September 2020 Call for Proposals! We are soliciting progressive, pioneering projects that will benefit and serve the R community and ecosystem at large. Our goal is to foster innovation and help bring your ideas into tangible realities. [bddy.me/2G9mXZA](#)



September 2020 ISC Call for Proposal...

The deadline for submitting proposals is midnight, October 1st, 2020. The [r-consortium.org](#)



Sep 27, 2020

South Africa

<https://cran.mirror.ac.za/>

Spain

<https://ftp.cixug.es/CRAN/>

<https://cran.rediris.es/>

Sweden

<https://ftpmirror1.infania.net/mirror/CRAN/>

<https://ftp.acc.umu.se/mirror/CRAN/>

Switzerland

<https://stat.ethz.ch/CRAN/>

Taiwan

<https://cran.csie.ntu.edu.tw/>

Thailand

<http://mirrors.psu.ac.th/pub/cran/>

Turkey

<https://cran.pau.edu.tr/>

<https://cran.gedik.edu.tr/>

<https://cran.ncc.metu.edu.tr/>

UK

<https://www.stats.bris.ac.uk/R/>

<https://cran.ma.imperial.ac.uk/>

USA

<https://mirror.las.iastate.edu/CRAN/>

<http://ftp.ussg.ju.edu/CRAN/>

<https://rweb.crmda.ku.edu/cran/>

<https://repo.miserver.it.umich.edu/cran/>

<http://cran.wustl.edu/>

<http://archive.linux.duke.edu/cran/>

<https://cran.case.edu/>

<https://ftp.osuosl.org/pub/CRAN/>

<http://lib.stat.cmu.edu/R/CRAN/>

<http://cran.mirrors.hoobly.com/>

<https://mirrors.nics.utk.edu/cran/>

<https://cran.revolutionanalytics.com/>

Uruguay

<https://espejito.fder.edu.uy/cran/>

TENET, Johannesburg

Oficina de software libre (CIXUG)

Spanish National Research Network, Madrid

Infania Networks

Academic Computer Club, Umeå University

ETH Zürich

National Taiwan University, Taipei

Prince of Songkla University, Hatyai

Pamukkale University, Denizli

Istanbul Gedik University

Middle East Technical University Northern Cyprus Campus, Mersin

University of Bristol

Imperial College London

Iowa State University, Ames, IA

Indiana University

University of Kansas, Lawrence, KS

MBNI, University of Michigan, Ann Arbor, MI

Washington University, St. Louis, MO

Duke University, Durham, NC

Case Western Reserve University, Cleveland, OH

Oregon State University

Statlib, Carnegie Mellon University, Pittsburgh, PA

Hoobly Classifieds, Pittsburgh, PA

National Institute for Computational Sciences, Oak Ridge, TN

Revolution Analytics, Dallas, TX

Facultad de Derecho, Universidad de la República



The Comprehensive R Archive Network

Download and Install R

Precompiled binary distributions of the base system and contributed packages, **Windows and Mac** users most likely want one of these versions of R:

- [Download R for Linux](#)
- [Download R for \(Mac\) OS X](#)
- [Download R for Windows](#)



R is part of many Linux distributions, you should check with your Linux package management system in addition to the link above.

Source Code for all Platforms

R for Windows

Subdirectories:

[base](#)

Binaries for base distribution. This is what you want to [install R for the first time](#).

[contrib](#)

Binaries of contributed CRAN packages (for R \geq 2.13.x; managed by Uwe Ligges). There is also information on [third party software](#) available for CRAN Windows services and corresponding environment and make variables.

[old contrib](#)

Binaries of contributed CRAN packages for outdated versions of R (for R $<$ 2.13.x; managed by Uwe Ligges).

[Rtools](#)

Tools to build R and R packages. This is what you want to build your own packages on Windows, or to build R itself.

Please do not submit binaries to CRAN. Package developers might want to contact Uwe Ligges directly in case of questions / suggestions related to Windows binaries.

You may also want to read the [R FAQ](#) and [R for Windows FAQ](#).

Note: CRAN does some checks on these binaries for viruses, but cannot give guarantees. Use the normal precautions with downloaded executables.

R-4.0.3 for Windows (32/64 bit)

[Download R 4.0.3 for Windows](#) (85 megabytes, 32/64 bit)

[Installation and other instructions](#)

[New features in this version](#)



If you want to double-check that the package you have downloaded matches the package distributed by CRAN, you can compare the [md5sum](#) of the .exe to the [fingerprint](#) on the master server. You will need a version of md5sum for windows: both [graphical](#) and [command line versions](#) are available.



安裝

RGui (64-bit)

檔案 編輯 視 其他 程式套件 視窗 輔助



```
R Console

R version 3.6.3 (2020-02-29) -- "Holding the Windsock"
Copyright (C) 2020 The R Foundation for Statistical Computing
Platform: x86_64-w64-mingw32/x64 (64-bit)

R 是免費軟體，不提供任何擔保。
在某些條件下您可以將其自由散布。
用 'license()' 或 'licence()' 來獲得散布的詳細條件。

R 是個合作計劃，有許多人為之做出了貢獻。
用 'contributors()' 來看詳細的情況並且
用 'citation()' 會告訴您如何在出版品中正確地參照 R 或 R 套件。

用 'demo()' 來看一些示範程式，用 'help()' 來檢視線上輔助檔案，或
用 'help.start()' 透過 HTML 瀏覽器來看輔助檔案。
用 'q()' 離開 R。

> |
```



rstudio



rstudio

All Images Videos News Maps More Settings Tools

About 9,140,000 results (0.57 seconds)

rstudio.com

RStudio | Open source & professional software for data ...

RStudio provides free and open source tools for R and enterprise-ready professional software for data science teams to develop and share their work at scale.

Results from rstudio.com

Download

RStudio is a set of integrated tools designed to help you ...



RStudio Server

Download - RStudio IDE Features - Download RStudio Server - ...

About RStudio

About RStudio · Our Inspiration People all over the world are ...

Pricing

RStudio Team Pricing - SMB Pricing Policy - Shiny Server Pro

RStudio Cloud

Data science without the hardware hassles. RStudio Cloud is a ...

RStudio IDE Features

RStudio is the premier integrated development environment for R ...



RStudio

Computer program

RStudio is an integrated development environment for R, a programming language for statistical computing and graphics. It is available in two formats: RStudio Desktop is a regular desktop application while RStudio Server runs on a remote server and allows accessing RStudio using a web browser. [Wikipedia](#)

Developer(s): RStudio, PBC

License: Affero General Public License v3


Stable release: 1.3.959 / 18 May 2020; 5 months ago

Operating system: Ubuntu, Fedora, Red Hat Linux, openSUSE, macOS, Windows NT


RStudio Desktop	RStudio Desktop Pro	RStudio Server	RStudio Server Pro
Open Source License	Commercial License	Open Source License	Commercial License
Free	\$995 /year	Free	\$4,975 /year (5 Named Users)
DOWNLOAD Learn more	BUY Learn more	DOWNLOAD Learn more	BUY Evaluation Learn more

RStudio Desktop 1.3.1093 - Release Notes


1. Install R. RStudio requires R 3.0.1+.
2. Download RStudio Desktop. Recommended for your system:



Requires Windows 10/8/7 (64-bit)



安裝



```
R version 3.6.3 (2020-02-29) -- "Holding the Windsock"  
Copyright (C) 2020 The R Foundation for Statistical Computing  
Platform: x86_64-w64-mingw32/x64 (64-bit)
```

R 是免費軟體，不提供任何擔保。
在某些條件下您可以將其自由散布。
用 `'license()'` 或 `'licence()'` 來獲得散布的詳細條件。

R 是個合作計劃，有許多人為之做出了貢獻。
用 `'contributors()'` 來看詳細的情況並且
用 `'citation()'` 會告訴您如何在出版品中正確地參照 R 或 R 套件。

用 `'demo()'` 來看一些示範程式，用 `'help()'` 來檢視線上輔助檔案，或
用 `'help.start()'` 透過 HTML 瀏覽器來看輔助檔案。
用 `'q()'` 離開 R。

```
> |
```

Environment is empty

Files**Plots****Packages****Help****Viewer**

Zoom



Export




- New File ▶
 - R Script Ctrl+Shift+N
 - R Notebook
 - R Markdown...
 - Shiny Web App...
 - Plumber API...
 - Text File
 - C++ File
 - Python Script
 - SQL Script
 - Stan File
 - D3 Script
 - R Sweave
 - R HTML
 - R Presentation
 - R Documentation
- New Project...
- Open File... Ctrl+O
- Recent Files ▶
- Open Project...
- Open Project in New Session...
- Recent Projects ▶
- Import Dataset ▶
- Save Ctrl+S
- Save As...
- Save All Ctrl+Alt+S
- Publish...
- Print...
- Close Ctrl+W
- Close All Ctrl+Shift+W
- Close All Except Current Ctrl+Alt+Shift+W
- Close Project
- Quit Session... Ctrl+Q

ndsock"
cal Computing

R 套件。

目 `help()` 來檢視線上輔助檔案，或
瀏覽器來看輔助檔案。






程式撰寫處

```
> |
```

用 'license()' 或 'licence()' 來獲得數布的詳細條件。

R 是個合作計劃，有許多人為之做出了貢獻。
用 'contributors()' 來看詳細的情況並且
用 'citation()' 會告訴您如何在出版品中正確地參照 R 或 R 套件。

用 'demo()' 來看一些示範程式；用 'help()' 來檢視線上輔助檔案，或
用 'help.start()' 透過 HTML 瀏覽器來看輔助檔案。
用 'q()' 離開 R。





常用

新增

開啟

資訊

儲存檔案

另存新檔

儲存為 Adobe PDF

歷程記錄

列印

共用

匯出

發佈

關閉

另存新檔

最近

個人



OneDrive - 個
ixf34@case.edu

其他位置



這台電腦



新增位置



瀏覽

另存新檔

<< Dropbox > IJUNG > 中山大學 課程 > 109-1 高中生物科學資優生培育計畫-高雄區 > Acute Inflammations Data Set

組合管理

新增資料夾

Acute Inflammations Data Set

bios_WEEK4

Microsoft Excel

Creative Cloud Files

Dropbox

HOME_竹榕禾樓

IJUNG

OneDrive

本機

3D 物件

下載

文件

音樂

桌面

圖片

影片

OS (C:)

DATA (D:)

名稱

修改日期

類型

Acute Inflammations Data Set

2020/11/13 下午 03:50

Microsoft Exce

檔案名稱(N): Acute Inflammations Data Set

存檔類型(T): CSV (逗號分隔)

作者: IJung Feng

標籤: 新增標記

標題: 新增標題

隱藏資料夾




```
R_code.R x
Source on Save
Run
Source
1
2 a <- 3
3 b <- 6
4
5 print(a+b)
6
7
```

```
R_code.R x
Source on Save
Run
Source
1
2 a <- 3
3 b <- 6
4
5 print(a+b)
6
7
8
```




```
Console Terminal x Jobs x
D:/Dropbox/1 JUNG/中山大學 課程/109-1 高中生物科學資優生培育計畫-高雄區/
> a <- 3
> b <- 6
>
> print(a+b)
[1] 9
> |
```

Save file



A screenshot of an R script editor window titled "R_code.R*". The toolbar at the top contains a save icon (floppy disk) which is highlighted with a red rectangle. A hand cursor is pointing at the save icon. Below the toolbar, the script content is as follows:

```
1  
2 a <-  
3 b <-  
4  
5 print(a+b)  
6
```



Add comment

```
R_code.R* x
Source on Save
1
2 # R program to add two numbers
3
4 # Assigning values to variables
5 a <- 9
6 b <- 4
7
8 # Printing sum
9 print(a + b) |
10
11
12
```

RStudio

File Edit Code View Plots Session Build Debug Profile To

R_code

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
10:1

Console

- Insert Section... Ctrl+Shift+R
- Jump To... Alt+Shift+J
- Go To File/Function... Ctrl+.
- Show Document Outline Ctrl+Shift+O
- Show Diagnostics
- Go To Help
- Go To Function Definition
- Extract Function Ctrl+Alt+X
- Extract Variable Ctrl+Alt+V
- Rename in Scope Ctrl+Alt+Shift+M
- Reflow Comment Ctrl+Shift+/
Comment/Uncomment Lines Ctrl+Shift+C
- Insert Roxygen Skeleton Ctrl+Alt+Shift+R
- Reindent Lines Ctrl+I
- Reformat Code Ctrl+Shift+A
- Run Selected Line(s) Ctrl+Enter
- Re-Run Previous Ctrl+Shift+P
- Run Region
- Run Selection as Local Job
- Send to Terminal Ctrl+Alt+Enter
- Source Ctrl+Shift+S
- Source with Echo Ctrl+Shift+Enter
- Source File... Ctrl+Alt+G

Set working directory. Read data.

```
R_code.R* x
Source on Save
Run Source
1
2 # First, set your working directory
3 setwd("D:/Dropbox/I JUNG/中山大學 課程/109-1 高中生物科學資優生培育計畫-高雄區/")
4
5 # Import the data and look at the first six rows
6 mydata <- read.csv(file = 'data/Acute Inflammations Data Set.csv')
7 head(mydata)
8 names(mydata)
```



```
D:/Dropbox/I JUNG/中山大學 課程/109-1 高中生物科學資優生培育計畫-高雄區/
> # First, set your working directory
> setwd("D:/Dropbox/I JUNG/中山大學 課程/109-1 高中生物科學資優生培育計畫-高雄區/")
>
> # Import the data and look at the first six rows
> mydata <- read.csv(file = 'data/Acute Inflammations Data Set.csv')
> head(mydata)
  Temperature  nausea Lumbar.pain Urine.pushing Micturition.pains Burning.of.urethra
1          35.5     no          yes             no                no                no
2          35.9     no           no             yes                yes                yes
3          35.9     no          yes             no                no                no
4          36.0     no           no             yes                yes                yes
5          36.0     no          yes             no                no                no
6          36.0     no          yes             no                no                no
```

Description	Windows & Linux	Mac
Clear console	Ctrl+L	Ctrl+L

No. of variables. No. of observations.

Column?
Row?

變項 variables

```
> mydata
```

	Temperature	nausea	Lumbar.pain	Urine.pushing	Micturition.pains	Burning.of.urethra
1	35.5	no	yes	no	no	no
2	35.9	no	no	yes	yes	yes
3	35.9	no	yes	no	no	no
4	36.0	no	no	yes	yes	yes
5	36.0	no	yes	no	no	no
6	36.0	no	yes	no	no	no
7	36.2	no	no	yes	yes	yes
8	36.2	no	yes	no	no	no
9	36.3	no	no	yes	yes	yes
10	36.6	no	no	yes	yes	yes
11	36.6	no	no	yes	yes	yes
12	36.6	no	yes	no	no	no
13	36.6	no	yes	no	no	no
14	36.7	no	no	yes	yes	yes
15	36.7	no	yes	no	no	no
16	36.7	no	yes	no	no	no
17	36.8	no	no	yes	yes	yes
18	36.8	no	no	yes	yes	yes
19	36.9	no	no	yes	yes	yes

觀察值
observations

No. of variables. No. of observations.

```
Console Terminal x Jobs x
D:/Dropbox/1 JUNG/中山大學 課程/109-1 高中生物科學資優生培育計畫-高雄區/
> # method 1
> nrow(mydata)
[1] 120
> colnames(mydata)
[1] "Temperature"      "nausea"           "Lumbar.pain"      "Urine.pushing"    "Micturition.pains"
[6] "Burning.of.urethra"
> ncol(mydata)
[1] 6
>
> # method 2
> dim(mydata)
[1] 120 6
>
```

Matrix

Row 1 → (6 10)
Row 2 → (5 3) ← An element of the matrix
Row 3 → (0 2)

Column 1 Column 2

Dimension of this matrix is 3 x 2

```
> mydata
  Temperature nausea Lumbar.pain Urine.pushing Micturition.pains Burning.of.urethra
1          35.5    no           yes           no                no                no
2          35.9    no           no            yes                yes                yes
3          35.9    no           yes           no                no                no
4          36.0    no           no            yes                yes                yes
5          36.0    no           yes           no                no                no
6          36.0    no           yes           no                no                no
7          36.2    no           no            yes                yes                yes
8          36.2    no           yes           no                no                no
9          36.3    no           no            yes                yes                yes
10         36.6    no           no            yes                yes                yes
11         36.6    no           no            yes                yes                yes
12         36.6    no           yes           no                no                no
13         36.6    no           yes           no                no                no
14         36.7    no           no            yes                yes                yes
15         36.7    no           yes           no                no                no
16         36.7    no           yes           no                no                no
17         36.8    no           no            yes                yes                yes
18         36.8    no           no            yes                yes                yes
19         36.9    no           no            yes                yes                yes
```

Creating new variables. [ifelse()] [AND、OR、NOT]

```
ifelse(test_expression, x, y)
```

```
> a = c(5,7,2,9)
```

```
> ifelse(a %% 2 == 0, "even", "odd")
```

```
[1] "odd" "odd" "even" "odd"
```

Arithmetic Operators

Operator	Description
+	addition
-	subtraction
*	multiplication
/	division
^ or **	exponentiation
x %% y	modulus (x mod y) 5%%2 is 1
x %/% y	integer division 5%/%2 is 2

Logical Operators

Operator	Description
<	less than
<=	less than or equal to
>	greater than
>=	greater than or equal to
==	exactly equal to
!=	not equal to
!x	Not x
x y	x OR y
x & y	x AND y
isTRUE(x)	test if X is TRUE

Cystitis_1

排尿困難且排尿疼痛

=AND(D2=1,E2=1)



	A	B	C	D	E	F	G	H
1	Temperature	nausea	Lumbar pain	Urine pushing	Micturition pains	Burning of urethra	Cystitis_1	
2	35.5	0	1	0	0	0	=AND(D2=1,E2=1)	
3	35.9	0	0	0	1	1		
4	35.9	0	1	1	0	0		
5	36	0	0	0	1	1		

```

10 # Creating new variables
11 # method 1
12 mydata$Cystitis_11 <- ifelse((mydata$Urine.pushing == "yes") & (mydata$Micturition.pains == "yes"), 1, 0)
13 head(mydata)
14

```

```

> head(mydata)
  Temperature nausea Lumbar.pain Urine.pushing Micturition.pains Burning.of.urethra Cystitis_11
1         35.5     no         yes           no           no           no           0
2         35.9     no         no           yes          yes           yes           1
3         35.9     no         yes          no           no           no           0
4         35.0     no         no           yes          yes           yes           1
5         35.0     no         yes          no           no           no           0
6         35.0     no         yes          no           no           no           0


```

Logical Operators

Operator	Description
<	less than
<=	less than or equal to
>	greater than
>=	greater than or equal to
==	exactly equal to
!=	not equal to
!x	Not x
x y	x OR y
x & y	x AND y
isTRUE(x)	test if X is TRUE

```
15 # method 2
16 attach(mydata)
17 mydata$Cystitis_12[(Urine.pushing == "yes") & (Micturition.pains == "yes")] <- 1
18 mydata$Cystitis_12[ ] <- 0
19 detach(mydata)
20 head(mydata)
21
```




練習



```

15 # method 2
16 attach(mydata)
17 mydata$Cystitis_12[(Urine.pushing == "yes") & (Micturition.pains == "yes")] <- 1
18 mydata$Cystitis_12[(Urine.pushing == "no") | (Micturition.pains == "no")] <- 0
19 detach(mydata)
20 head(mydata)
21

```



(Urine.pushing == "no") AND (Micturition.pains == "no")

```

> head(mydata)
  Temperature  nausea Lumbar.pain Urine.pushing Micturition.pains Burning.of.urethra Cystitis_11 Cystitis_12
1          35.5     no         yes           no           no           no           0           0
2          35.9     no          no           yes           yes           yes           1           1
3          35.9     no         yes           no           no           no           0           0
4          36.0     no          no           yes           yes           yes           1           1
5          36.0     no         yes           no           no           no           0           0
6          36.0     no         yes           no           no           no           0           0

```

No. of conditional observations.

```
29 # method 1
30 nrow(mydata[mydata$Cystitis_11==1,])
31 nrow(mydata[mydata$Cystitis_12==1,])
32
33 # method 2
34 attach(mydata)
35 nrow(mydata[Cystitis_11==1,])
36 nrow(mydata[Cystitis_12==1,])
37 detach(mydata)
```

```
> # method 1
> nrow(mydata[mydata$Cystitis_11==1,])
[1] 49
> nrow(mydata[mydata$Cystitis_12==1,])
[1] 49
>
> # method 2
> attach(mydata)
> nrow(mydata[Cystitis_11==1,])
[1] 49
> nrow(mydata[Cystitis_12==1,])
[1] 49
> detach(mydata)
```

```
29 # method 1
30 nrow(mydata[mydata$Cystitis_11==0,])
31 nrow(mydata[mydata$Cystitis_12==0,])
32
33 # method 2
34 attach(mydata)
35 nrow(mydata[Cystitis_11==0,])
36 nrow(mydata[Cystitis_12==0,])
37 detach(mydata)
```

```
> # method 1
> nrow(mydata[mydata$Cystitis_11==0,])
[1] 71
> nrow(mydata[mydata$Cystitis_12==0,])
[1] 71
>
> # method 2
> attach(mydata)
> nrow(mydata[Cystitis_11==0,])
[1] 71
> nrow(mydata[Cystitis_12==0,])
[1] 71
> detach(mydata)
```

Cystitis_1

排尿困難且排尿疼痛

49位膀胱炎 + 71位非膀胱炎 = 120位

(確認是否與總數相符合)

	A	B	C	D	E	F	G
1	Temperature	nausea	Lumbar pain	Urine pushing	Micturition pains	Burning of urethra	Cystitis_1
2	35.5	0	1	0	0	0	FALSE
3	35.9	0	0	0	1	1	TRUE
4	35.9	0	1	0	0	0	FALSE
5	36	0	0	1	1	1	TRUE


	A	B	C	D	E	F	G
1	Temperature	nausea	Lumbar pain	Urine pushing	Micturition pains	Burning of urethra	Cystitis_1

確認是否
Cystitis_1 = "TRUE" 時
Urine pushing=1 且 Micturition pains=1

Cystitis_1 = "FALSE" 時
Urine pushing=? Micturition pains=?
至少一個=0?

49 + 71 = 120 check

10	36.3	0	0	1	1	1
11	36.6	0	0	1	1	1
12	36.6	0	0	1	1	1



確定 取消

練習

- Cystitis_1

排尿困難且排尿疼痛

=AND(D2=1,E2=1)

- Cystitis_2

排尿困難或排尿疼痛或尿道灼熱

=OR(C2=1,D2=1,E2=1)

符合排尿困難或排尿疼痛或尿道灼熱之**膀胱炎**與**非膀胱炎**定義患者各有幾位?

```
44 #-----
45 # Exercise
46 # Creating new variables Cystitis_2
47 # method 1
48 mydata$Cystitis_21 <- ifelse( (mydata$Urine.pushing == "yes") | (mydata$Micturition.pains == "yes") | (mydata$Burning.of.urethra == "yes")), 1, 0)
49 head(mydata)
50
51 # method 2
52 attach(mydata)
53 mydata$Cystitis_22 <- 0
54 mydata$Cystitis_22[(Burning.of.urethra == "yes") | (Urine.pushing == "yes") | (Micturition.pains == "yes")] <- 1
55 detach(mydata)
56 head(mydata)
57
58 |
59 # check no. of Cystitis_2
60 # method 1
61 nrow(mydata[mydata$Cystitis_21==1,])
62 nrow(mydata[mydata$Cystitis_22==1,])
63
64 # method 2
65 attach(mydata)
66 nrow(mydata[Cystitis_21==1,])
67 nrow(mydata[Cystitis_22==1,])
68 detach(mydata)
69
70
71 # check no. of no Cystitis_2
72 # method 1
73 nrow(mydata[mydata$Cystitis_21==0,])
74 nrow(mydata[mydata$Cystitis_22==0,])
75
76 # method 2
77 attach(mydata)
78 nrow(mydata[Cystitis_21==0,])
79 nrow(mydata[Cystitis_22==0,])
80 detach(mydata)
81
```

```
> head(mydata)
  Temperature nausea Lumbar.pain Urine.pushing Micturition.pains Burning.of.urethra Cystitis_11 Cystitis_12 Cystitis_21 Cystitis_22
1         35.5    no         yes         no         no         no         0         0         0         0
2         35.9    no         no         yes         yes         yes         1         1         1         1
3         35.9    no         yes         no         no         no         0         0         0         0
4         36.0    no         no         yes         yes         yes         1         1         1         1
5         36.0    no         yes         no         no         no         0         0         0         0
6         36.0    no         yes         no         no         no         0         0         0         0
```

```
> # check no. of Cystitis_2
> # method 1
> nrow(mydata[mydata$Cystitis_21==1,])
[1] 90
> nrow(mydata[mydata$Cystitis_22==1,])
[1] 90
>
> # method 2
> attach(mydata)
> nrow(mydata[Cystitis_21==1,])
[1] 90
> nrow(mydata[Cystitis_22==1,])
[1] 90
> detach(mydata)
>
>
> # check no. of no Cystitis_2
> # method 1
> nrow(mydata[mydata$Cystitis_21==0,])
[1] 30
> nrow(mydata[mydata$Cystitis_22==0,])
[1] 30
>
> # method 2
> attach(mydata)
> nrow(mydata[Cystitis_21==0,])
[1] 30
> nrow(mydata[Cystitis_22==0,])
[1] 30
> detach(mydata)
```



Nephritis_D

若 體溫 $\geq 38^{\circ}\text{C}$ 且 腰椎疼痛 [Lumber pain]
Nephritis_D 就 等於 1,
否則 Nephritis_D 等於 0

= IF(AND(A2 >= 38, C2 = 1), 1, 0)

	A	B	C	D	E	F	G	H	I	J	K
1	Temperature	nausea	Lumbar pain	Urine pushing	Micturition pains	Burning of urethra	Cystitis_1	Cystitis_2	Nephritis_1		
2	35.5	0	1	0	0	0	FALSE	FALSE	= IF(AND(A2 >= 38, C2 = 1), 1, 0)		
3	35.9	0	0	1	1	1	TRUE	TRUE	0		
4	35.9	0	1	0	0	0	FALSE	FALSE	0		

```
82 #-----
83
84 # Creating new variables Nephritis_D
85 # method 1
86 mydata$Nephritis_D1 <- ifelse((mydata$Temperature >=38) & (mydata$Lumbar.pain == "yes"), 1, 0)
87 head(mydata)
88
89 # method 2
90 attach(mydata)
91 mydata$Nephritis_D2 <- 0
92 mydata$Nephritis_D2[(Temperature >=38)&(Lumbar.pain == "yes")] <- 1
93 detach(mydata)
94 head(mydata)
95
96 # check no. of Nephritis_D1 Nephritis_D2
97 # method 1
98 nrow(mydata[mydata$Nephritis_D1==1,])
99 nrow(mydata[mydata$Nephritis_D2==1,])
100
101 # method 2
102 attach(mydata)
103 nrow(mydata[Nephritis_D1==1,])
104 nrow(mydata[Nephritis_D2==1,])
105 detach(mydata)
106 |
107 # check no. of Nephritis_D1 Nephritis_D2
108 # method 1
109 nrow(mydata[mydata$Nephritis_D1==0,])
110 nrow(mydata[mydata$Nephritis_D2==0,])
111
112 # method 2
113 attach(mydata)
114 nrow(mydata[Nephritis_D1==0,])
115 nrow(mydata[Nephritis_D2==0,])
116 detach(mydata)
```

```

> detach(mydata)
> # Creating new variables Nephritis_D
> # method 1
> mydata$Nephritis_D1 <- ifelse((mydata$Temperature >=38) & (mydata$Lumbar.pain == "yes"), 1, 0)
> head(mydata)

```

	Temperature	nausea	Lumbar.pain	Urine.pushing	Micturition.pains	Burning.of.urethra	Cystitis_11	Cystitis_12	Cystitis_21	Cystitis_22	Nephritis_D1	Nephritis_D2
1	35.5	no	yes	no	no	no	0	0	0	0	0	0
2	35.9	no	no	yes	yes	yes	1	1	1	1	0	0
3	35.9	no	yes	no	no	no	0	0	0	0	0	0
4	36.0	no	no	yes	yes	yes	1	1	1	1	0	0
5	36.0	no	yes	no	no	no	0	0	0	0	0	0
6	36.0	no	yes	no	no	no	0	0	0	0	0	0

```

>
> # method 2
> attach(mydata)
> mydata$Nephritis_D2 <- 0
> mydata$Nephritis_D2[(Temperature >=38)&(Lumbar.pain == "yes")] <- 1
> detach(mydata)
> head(mydata)

```

	Temperature	nausea	Lumbar.pain	Urine.pushing	Micturition.pains	Burning.of.urethra	Cystitis_11	Cystitis_12	Cystitis_21	Cystitis_22	Nephritis_D1	Nephritis_D2
1	35.5	no	yes	no	no	no	0	0	0	0	0	0
2	35.9	no	no	yes	yes	yes	1	1	1	1	0	0
3	35.9	no	yes	no	no	no	0	0	0	0	0	0
4	36.0	no	no	yes	yes	yes	1	1	1	1	0	0
5	36.0	no	yes	no	no	no	0	0	0	0	0	0
6	36.0	no	yes	no	no	no	0	0	0	0	0	0

```
> # check no. of Nephritis_D1 Nephritis_D2
> # method 1
> nrow(mydata[mydata$Nephritis_D1==1,])
[1] 50
> nrow(mydata[mydata$Nephritis_D2==1,])
[1] 50
>
> # method 2
> attach(mydata)
> nrow(mydata[Nephritis_D1==1,])
[1] 50
> nrow(mydata[Nephritis_D2==1,])
[1] 50
> detach(mydata)
>
> # check no. of Nephritis_D1 Nephritis_D2
> # method 1
> nrow(mydata[mydata$Nephritis_D1==0,])
[1] 70
> nrow(mydata[mydata$Nephritis_D2==0,])
[1] 70
>
> # method 2
> attach(mydata)
> nrow(mydata[Nephritis_D1==0,])
[1] 70
> nrow(mydata[Nephritis_D2==0,])
[1] 70
> detach(mydata)
```

練習

- Cystitis_D

條件1:

體溫 < 38°C 且 排尿困難 [Urine pushing]

條件2:

排尿困難 [Urine pushing] 且 排尿疼痛 [Micturition pains]

若 符合條件1 或是 條件2
則 Cystitis_D 就 等於 1,
否則 Cystitis_D 等於 0

IF、OR、AND

```
124
125 # Creating new variables Cystitis_D
126
127 # method 1
128 mydata$Cystitis_C11 <- ifelse((mydata$Temperature < 38) & (mydata$Urine.pushing == "yes"), 1, 0)
129 mydata$Cystitis_C21 <- ifelse((mydata$Urine.pushing == "yes") & (mydata$Micturition.pains == "yes"), 1, 0)
130 mydata$Cystitis_D1 <- ifelse((mydata$Cystitis_C11==1) | (mydata$Cystitis_C21==1),1,0)
131
132 head(mydata)
133
134 # method 2
135 attach(mydata)
136 mydata$Cystitis_C12 <- 0
137 mydata$Cystitis_C12[(Temperature < 38)&(Urine.pushing == "yes")] <- 1
138 mydata$Cystitis_C22 <- 0
139 mydata$Cystitis_C22[(Urine.pushing == "yes")&(Micturition.pains == "yes")] <- 1
140 mydata$Cystitis_D2 <- 0
141 mydata$Cystitis_D2[(Cystitis_C12 ==1)|(Cystitis_C22 == 1)] <- 1
142 detach(mydata)
143 head(mydata)
144
145 # check no. of Cystitis_D1 Cystitis_D2
146 # method 1
147 nrow(mydata[mydata$Cystitis_D1==1,])
148 nrow(mydata[mydata$Cystitis_D2==1,])
149
150 # method 2
151 attach(mydata)
152 nrow(mydata[Cystitis_D1==1,])
153 nrow(mydata[Cystitis_D2==1,])
154 detach(mydata)
155
156 # check no. of Nephritis_D1 Nephritis_D2
157 # method 1
158 nrow(mydata[mydata$Cystitis_D1==0,])
159 nrow(mydata[mydata$Cystitis_D2==0,])
160
161 # method 2
162 attach(mydata)
163 nrow(mydata[Cystitis_D1==0,])
164 nrow(mydata[Cystitis_D2==0,])
165 detach(mydata)
166
```


```
> # check no. of Cystitis_D1 Cystitis_D2
> # method 1
> nrow(mydata[mydata$Cystitis_D1==1,])
[1] 59
> nrow(mydata[mydata$Cystitis_D2==1,])
[1] 59
>
> # method 2
> attach(mydata)
> nrow(mydata[Cystitis_D1==1,])
[1] 59
> nrow(mydata[Cystitis_D2==1,])
[1] 59
> detach(mydata)
>
> # check no. of Nephritis_D1 Nephritis_D2
> # method 1
> nrow(mydata[mydata$Cystitis_D1==0,])
[1] 61
> nrow(mydata[mydata$Cystitis_D2==0,])
[1] 61
>
> # method 2
> attach(mydata)
> nrow(mydata[Cystitis_D1==0,])
[1] 61
> nrow(mydata[Cystitis_D2==0,])
[1] 61
> detach(mydata)
```

*“**Knowledge** is the collection of skills and information a person has acquired through experience. **Intelligence** is the ability to apply knowledge.”*

“Knowledge is wonderful, but it fades as techniques and technologies come and go. Intelligence sustains. Its borders extend beyond any technique or technology, and that makes all the difference.”

Anthony Colangelo

台北醫學大學附設醫院院長陳瑞杰 | 最懂區塊鏈的院長：智慧醫院只是手段，變成「好醫院」才是目的



台北醫學大學附設醫院院長陳瑞杰認為，智慧醫療的最終目的是透過智慧科技變成「好醫院」。 圖片來源：台北醫學大學附設醫院 首圖設計：yao ting

Thank You
For
Your Attention!

Any Questions?

回家作業

E-mail: ijfeng@g-mail.nsysu.edu.tw

Title: [109-1 高中生物科學資優生培育計畫-高雄區_姓名_學號]

答案 [PPT]

程式碼 [R]

Echocardiogram Data Set 心臟超音波資料集

Donor: Steven Salzberg and Dr. Evlin Kinney

變項編號	變項英文名稱	變項中文名稱	單位		解釋
V1	age-at-heart-attack	心臟病發病年齡	year(s)	連續變項	
V2	pericardial-effusion	心包膜積水		0:無(no) 1:有(yes)	
V3	fractional-shortening	短縮分率			左心收縮力指標之一，數值越高越不正常。
V4	epss	epss			E-point septal separation。左心收縮力指標之一，數值越高越不正常。
V5	lvdd	左心室舒張末期內徑			left ventricular end-diastolic dimension。舒張末期心臟大小，數值越大越不正常。
V6	wall-motion-index	室壁運動記分指數			室壁運動異常程度，數值越高越不正常。

1. 共有___ 觀察值, 有___個變項。

我們欲根據心臟超音波研究結果找出有哪些心臟病發患者心臟病發後生存年份短於1年。

研究發現年齡大於65歲老年人, 若 fractional-shortening大於等於0.15 且 EPSS大於等於10且LVDD大於等於4.5 且 wall-motion-index大於1.0 則患者存活時間短於1年。

1. 有幾位病患 心臟病發病時年齡大於等於65 歲?_____

2. 有幾位病患 fractional-shortening大於等於0.15?_____

3. 有幾位病患 EPSS大於等於10?_____

4. 有幾位病患 LVDD大於等於4.5?_____

5. 有幾位病患 wall-motion-index大於1.0?_____

6. 2~6條件皆符合得有幾位? _____

研究另外發現年齡小於65歲者, 雖然fractional-shortening小於0.15, 但是EPSS、LVDD與wall-motion-index 3項其中2項以上符合更為嚴苛的條件時, 患者存活時間短於1年。

7. 有幾位病患 心臟病發病時年齡小於65 歲? _____

8. 有幾位病患 fractional-shortening小於0.15? _____

9. 有幾位病患 EPSS大於等於15? _____

10. 有幾位病患 LVDD大於等於4.5? _____

11. 有幾位病患 wall-motion-index大於2.0? _____

12. 有幾位病患符合條件9、10、11中2項以上者? _____

13. 有幾位病患符合條件7 且條件8且條件12者? _____

14. 根據研究所發現特徵, 請問共有幾位患者存活時間短於1年 (符合條件6或是條件13)? _____